



- NOTES:  
 1. MATERIAL:  
 2. FINISH:  
 3. PART IS TO BE FREE OF OIL AND CONTAMINATION.  
 4. ALL INTERNAL BEND RADII ARE PER STANDARD INDUSTRY PRACTICES FOR MATERIAL BEING USED, UNLESS OTHERWISE SPECIFIED.  
 5. ALL SHARP EDGES MUST BE REMOVED.  
 6. TOLERANCE CLASS:  
 7. \* THIS SYMBOL INDICATED CRITICAL DIMENSION

TOL.±			✓					✓	✓	COMMENTS:
RANGE	N1	N2	M1	M2	S1	S2	CN	φ	ANG.	
0~6	0.20	0.25	0.15	0.20	0.05	0.10	0.50	0.05	0~30° ±0.1°	
6~30	0.20	0.25	0.15	0.25	0.10	0.15	1.00		31°~60° ±0.8°	
30~120	0.25	0.35	0.20	0.30	0.20	0.40	2.00		61°~90° ±0.5°	
120~300	0.30	0.35	0.25	0.40	0.40	0.80	3.00			
300~600	0.40	0.50	0.30	0.50	0.50	1.00	3.00			
600~1200	0.50	0.60	0.40	0.60	0.60	1.20	4.00			

Part IV			Name	Date
Part III		Designed by	Benson	20120423
Part II		Checked by		
Part I		Approved by	Leo	20120423
NEXT ASSY	USED ON	Material	Finished	
APPLICATION		Rev	Scale	Sheet
		A01	1:1	1/1
		Units	mm	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Axiomtek. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Axiomtek IS PROHIBITED.				
Part Name		Title		
DSB310-110		File Name		

RevNo	Revision note	Date	Signature	Checked

*Revisions*